

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/720,387	11/25/2003	Manabu Minowa	OKI.598	4269
20987	7590 05/25/2006		EXAMINER	
VOLENTINE FRANCOS, & WHITT PLLC ONE FREEDOM SQUARE			AMAYA, CARLOS DAVID	
	DOM SQUARE DOM DRIVE SUITE 12	60	ART UNIT	PAPER NUMBER
RESTON, V	A 20190		2836	-

DATE MAILED: 05/25/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

• •		·	1.1
	Application No.	Applicant(s)	- U ^
	10/720,387	MINOWA, MANABU	
Office Action Summary	Examiner	Art Unit	
	Carlos Amaya	2836	
The MAILING DATE of this communication a Period for Reply	appears on the cover sheet w	ith the correspondence address	
A SHORTENED STATUTORY PERIOD FOR REF WHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CFR after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory peri - Failure to reply within the set or extended period for reply will, by sta Any reply received by the Office later than three months after the ma earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNI 1.136(a). In no event, however, may a od will apply and will expire SIX (6) MO tute, cause the application to become A	CATION. reply be timely filed NTHS from the mailing date of this communication. BANDONED (35.U.S.C. 8.133)	
Status			
Responsive to communication(s) filed on 25 This action is FINAL . 2b) ☑ T Since this application is in condition for allow closed in accordance with the practice under	his action is non-final. wance except for formal mat		
Disposition of Claims		. 11, 100 0.0. 210.	
4) Claim(s) 1-3 is/are pending in the applicatio 4a) Of the above claim(s) is/are withd 5) Claim(s) is/are allowed. 6) Claim(s) 1-3 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and	lrawn from consideration.		
Application Papers			
9) ☐ The specification is objected to by the Exam 10) ☑ The drawing(s) filed on 25 November 2003 is Applicant may not request that any objection to t Replacement drawing sheet(s) including the corn 11) ☐ The oath or declaration is objected to by the	s/are: a) accepted or b) the drawing(s) be held in abeyatection is required if the drawing	nce. See 37 CFR 1.85(a). g(s) is objected to. See 37 CFR 1.121(d).	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority docume 2. Certified copies of the priority docume 3. Copies of the certified copies of the papplication from the International Burn * See the attached detailed Office action for a light	ents have been received. ents have been received in a riority documents have been eau (PCT Rule 17.2(a)).	Application No received in this National Stage	·
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/Paper No(s)/Mail Date	Paper No	Summary (PTO-413) (s)/Mail Date Informal Patent Application (PTO-152)	

DETAILED ACTION

Drawings

1. Figures 2 and 3 should be designated by a legend such as --Prior Art-- because only that which is old is illustrated. See MPEP § 608.02(g). Corrected drawings in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-3 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura (JP 06042575) in view of Kimura (US 5,016,223).

With respect to claim 1 Nakamura in view of Kimura discloses an interface circuit for inputting/outputting a signal between first and second apparatuses (Circuit 1 and Circuit 2 Figure 1) having different power units (Power source 3 and 4), respectively, comprising: a power node to which a first power voltage that is supplied from the power unit of said first apparatus is outputted (Power node being the point at which the Power

source 3 is connected to Circuit 1); a 3-state buffer (3 State buffer 6) which is driven by a second power voltage that is supplied from the power unit of said second apparatus (As shown in figure 1 buffer 6 is driven power source 4 of second apparatus) and in which the output of the signal that is supplied from said second apparatus is controlled by an electric potential at said power node (Figure 1 shows buffer 6 receiving a control signal from the second apparatus; also the buffer receives a Vdd electric potential as shown in circuit 1 from the electrical node).

Nakamura, however, does not disclose an analog switch which is driven by said second power voltage and in which a connection between an output side of said 3- state buffer and a logic circuit in said first apparatus is controlled by the electric potential at said power node.

Kimura discloses a memory card circuit with a 3 state buffer (34,35) and analog switch 30 shown in figure 5 (a), the analog switch 30 is for controlling a signal (Kimura's invention is being used only to show that analog switches are used to control signals).

It would have been obvious at the time the invention was made to have included Kimura's analog switch in Nakamura's invention.

The suggestion or motivation for doing so would have been to provide an analog switch, which depending upon a received signal control its operation it turns on/off preventing/allowing power/signal to flow.

With respect to claim 2 Nakamura in view of Kimura discloses an interface circuit for inputting/outputting a signal between first and second apparatuses (Circuit 1 and Circuit 2 Figure 1) having different power units (Power source 3 and 4), respectively,

Application/Control Number: 10/720,387

Art Unit: 2836

comprising: a power node to which a first power voltage that is supplied from the power unit of said first apparatus is outputted (Power node being the point at which the Power source 3 is connected to Circuit 1); a voltage detector which detects a voltage at said power node and outputs a control signal when said voltage exceeds a reference voltage (Sag detectors in figures 1-3, which detects a predetermined potential difference in the supply voltage, Paragraph 0018, lines 12-14); a 3-state buffer (3 State buffer 6) which is driven by a second power voltage that is supplied from the power unit of said second apparatus (As shown in figure 1 buffer 6 is driven power source 4 of second apparatus) and in which the output of the signal that is supplied from said second apparatus is controlled by an electric potential at said power node (Figure 1 shows buffer 6 receiving a control signal from the second apparatus; also the buffer receives a Vdd electric potential as shown in circuit 1 from the electrical node).

Nakamura, however, does not disclose an analog switch, which is driven by, said second power voltage and in which a connection between an output side of said 3- state buffer and a logic circuit in said first apparatus is controlled by said control signal.

It would have been obvious at the time the invention was made to have included Kimura's analog switch in Nakamura's invention.

The suggestion or motivation for doing so would have been to provide an analog switch, which depending upon a received signal control its operation it turns on/off preventing/allowing power/signal to flow.

With respect to claim 3 Nakamura in view of Kimura discloses 3. An interface circuit for inputting/outputting a signal between first and second apparatuses having

Application/Control Number: 10/720,387

Art Unit: 2836

different power units, respectively, comprising: a power node to which a first power voltage that is supplied from the power unit of said first apparatus is outputted (Power node being the point at which the Power source 3 is connected to Circuit 1, Vdd); a voltage detector which outputs a control signal when a voltage at said power node exceeds a reference voltage (Sag detectors in figures 1-3, which detects a predetermined potential difference in the supply voltage, Paragraph 0018, lines 12-14, depending on the sense change in the supply voltage a control signal is emitted to the buffers. Power node being voltage at Vdd being supply to the sag detector); a 3-state buffer which is driven by a second power voltage that is supplied from the power unit of said second apparatus (As shown in figure 1 buffer 6 is driven power source 4 of second apparatus), controls the signal that is supplied from said second apparatus in accordance with a voltage that is applied to a control terminal and supplies said signal to a logic circuit in said first circuit (Output of buffer 6 in circuit 1 is outputted to the circuit 2 to cease operation of the receiving circuit 2).

Nakamura, however, does not disclose an analog switch that is driven by said second power voltage and in which a connection between said power node and the control terminal of said 3-state buffer is controlled by said control signal.

It would have been obvious to a person of ordinary skill in the art at time the invention was made to connect an analog switch as disclosed by Kimura, in Nakamura's invention and, which is controlled by the control signal generated by the voltage detector.

Application/Control Number: 10/720,387

Art Unit: 2836

Page 6

The suggestion or motivation for doing so would have been to provide an analog switch, which depending upon a received signal control its operation it turns on/off preventing/allowing power/signal to flow.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to the examiner's supervisor, Brian Sircus who can be reached on (571)272-2800. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

CA

PHUONGT.VU